

SAFETY DATA SHEET

SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: ALUMINUM SULFATE SOLUTION
Control Number: 00069
Product Description: Sulfate Salt

COMPANY IDENTIFICATION

Supplier: Chemical Distribution Solutions
1125 Oak St. Ste. 303
Conway, AR 72032

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC
General Information: (501) 978-1111

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification:

[Health]

Serious Eye Damage, Category 2

[Environmental]

Acute Aquatic Toxicity Category 3

[Physical]

Corrosive

GHS Label elements, including precautionary statements

Pictograms



Signal Word: Warning

Hazard statement(s)

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 IF INHALED: Remove victim to fresh air and keep.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS Number	%WT
Aluminum Sulfate	10043-01-3	48.5

SAFETY DATA SHEET

SECTION 4 - FIRST AID MEASURES

FIRST AID PROCEDURES:

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Seek medical attention.

Skin Contact: Wash with soap and water. Seek medical attention if irritation develops.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms appear.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous combustion products: Oxides of carbon, sulfur and various hydrocarbons

Fire Fighting Procedures: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Unusual Fire and Explosion Hazards: Material is noncombustible and is not expected to present a hazard.

SECTION 6 - ACCIDENTAL RELEASE and DISPOSAL MEASURES

Dilute small spills or leaks cautiously with plenty of water. Neutralize any further residue with alkali such as soda ash, lime or limestone. Adequate ventilation is required if soda ash or limestone is used, because of the consequent release of carbon dioxide gas. Large spills should be diked up with soda ash and neutralized as above. Collect liquid and/or residue and dispose of in accordance with applicable regulations.

SECTION 7 - STORAGE AND HANDLING

Keep container tightly closed when not in use. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors or mists. Remove contaminated clothing and wash thoroughly after handling. Keep storage container tightly closed. Store in a cool, dry, well-ventilated area or cabinet. Isolate from incompatible substances. Store in plastic or rubber-lined containers.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: Aluminum Sulfate 2 mg/m³ ACGIH; 5 mg/m³ OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions, potential exposure conditions and may include gloves, boots, suits and other protective items.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

SAFETY DATA SHEET

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: Not applicable
Autoignition Temperature: No Available Data
Boiling Point: No Available Data
Melting Point/Freezing Point: 190 °F
Vapor Pressure: No Available Data
Vapor Density (Air-1): No Available Data
Odor/Appearance: Clear liquid no appreciable odor.

Flammability Limits: Not applicable
Specific Gravity: 1.33
Volatile %: No Available Data
Evaporation Rate (Water=1):
pH: 3.5
Solubility in Water: Complete

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions.
Conditions to Avoid: Keep away from incompatibles.
Incompatible Materials: Strong oxidizers.
Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: Contact can cause redness and irritation. Severity depends on the amount and duration of exposure.

Eyes: Vapors are irritating to the eyes. Liquid contact will cause stinging and tearing.

Inhalation: Excessive inhalation of high concentrations may be harmful. Mist or vapor can irritate the throat and lungs.

Ingestion: If swallowed this material may irritate the mucous membranes of the mouth throat and esophagus. Aspiration of this material into the lungs may result in damage.

Acute oral toxicity:

LD50 rat: 1930 mg/kg

Acute inhalation toxicity:

LD50 rat: No available data

Acute dermal toxicity:

LD50 rabbit: No available data

SECTION 12 - ECOLOGICAL INFORMATION

Aquatic Toxicity: No available data

Bio-accumulative potential: No available data

Mobility: Accidental spillage may lead to penetration in the soil and contamination of groundwater.

SECTION 13 - DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 - TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name: Corrosive Liquid, acidic, inorganic, n.o.s. (Aluminum Sulfate)
Hazard Class 8
UN Number: 3264
Packaging Group: 3

SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. The reportable quantity (RQ) for this material is 5000 pounds. If appropriate, immediately report to the National Response Center (800/424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Acute Health Hazard

SARA Section 313 (40 CFR 372) Hazard Categories:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

The following components are subject to reporting levels established by SARA Title III, Section 313:

Clean Water Act: This product contains Aluminum Sulfate chemicals that are listed under the CWA.

Clean Air Act: This product contains no chemicals that are listed under the CAA.

California Prop 65: This product contains no chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 - OTHER INFORMATION

MSDS Revision Date: September 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 1
Flammability: 0
Reactivity: 0

The data in this Safety Data Sheet relates to the specific material designated and does not relate to its use in combination with any other material or process. The data contained is believed to be correct. However, since conditions of use are outside our control it should not be taken as warranty or representation for which Chemical Distribution Solutions assumes legal responsibility. This information is provided solely for your consideration, investigation, and verification.