

SAFETY DATA SHEET

CHEMICAL DISTRIBUTION SOLUTIONS

SECTION 1 - COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: ISOBUTYL ACETATE

Control Number: 00192

Product Description: Solvent

COMPANY IDENTIFICATION

Supplier: Chemical Distribution Solutions

1125 Oak St. Ste. 303

Conway, AR 72032

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

General Information: (501) 978-1111

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification:

[Health]

None

[Environmental]

None

[Physical]

Flammable Liquid Category 3

GHS Label elements, including precautionary statements

Pictograms



Signal Word: Warning

Hazard statement(s)

H225 Highly flammable liquid and vapor.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTSCHEMICAL

CHEMICAL NAME	CAS Number	%WT
Isobutyl acetate	110-19-0	100

SAFETY DATA SHEET

CHEMICAL DISTRIBUTION SOLUTIONS

SECTION 4 - FIRST AID MEASURES

Eyes: Flush with running water for several minutes. Seek medical attention if irritation persists.

Skin: Wash exposed skin with soap and water. Seek medical attention if irritation persists.

Inhalation: For excessive inhalation remove to fresh air. If breathing is difficult seek medical attention.

Ingestion: DO NOT induce vomiting. Rinse mouth with water. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Extinguishing Media: To extinguish flames use water spray, dry chemical, carbon dioxide or fire fighting foam. .

Fire Fighting Procedures: Cool exposed containers with water spray. Wear self-contained breathing apparatus (SCBA) operated in pressure demand mode and full bunker firefighter's protective clothing.

Fire and Explosion Hazards: Containers can rupture or explode under fire conditions due to pressure and vapor buildup. Heated vapors may form explosive mixture with air. Vapors may travel across the ground and reach an ignition source.

SECTION 6 - ACCIDENTAL RELEASE and DISPOSAL MEASURES

Small Spill: Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large Spill: Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Be careful that the product is not present at a concentration level above TLV.

SECTION 7 - STORAGE AND HANDLING

Handling and Storage: Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, metals, acids.

Storage: Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: Isobutyl Acetate 150 ppm ACGIH 200 ppm OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

Other Equipment: Adequate explosion proof ventilation to control airborne concentrations below the exposure limits. Eye wash station and drenching shower in close proximity to use are advised.

SAFETY DATA SHEET

CHEMICAL DISTRIBUTION SOLUTIONS

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: 72 °F
Autoignition Temperature: 565 °F
Boiling Point: 239 °F
Melting Point: -146 °F
Vapor Pressure: 15 mmHg
Vapor Density (Air-1): 4
Odor/Appearance: Colorless liquid with fruit-like odor.

Flammability Limits: Lower 1 Upper 11
Specific Gravity: 0.867
Volatile %: No available data
Evaporation Rate (BuAc=1): No available data
pH: 6.2
Solubility in Water: No available data

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions.
Conditions to Avoid: Keep away from heat, flame and other potential ignition sources.
Materials to Avoid: Highly reactive with oxidizing agents, metals, acids.
Decomposition Products: When combusted, oxides of carbon and various hydrocarbons.

SECTION 11 - TOXICOLOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: May irritate the skin. Prolonged or repeated contact may cause dermatitis.
Eyes: Causes moderate eye irritation. Symptoms of redness and tearing.
Inhalation: Vapors may be irritating to the respiratory tract. May cause coughing and sneezing.
Ingestion: Causes irritation of the mouth and throat.

Acute oral toxicity:

LD50 rat: 13,400 mg/kg

Acute inhalation toxicity:

LC50 rat: No available data

Acute dermal toxicity:

LD50 rabbit: > 17,400 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: Toxicity to fish LC50 - *Leuciscus idus melanotus* - 101 mg/l - 48 h
Bio-accumulative potential: Bioaccumulation of this product is unlikely. This product is readily biodegradable.
Mobility: This product is not considered mobile in soil and likely to volatilize from soil surface.

SECTION 13 - DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 - TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name: Isobutyl Acetate
Hazard Class: 3
UN Number: 1213
Packaging Group: 2

SAFETY DATA SHEET

SECTION 15 · REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Fire Hazard.

SARA Section 313 (40 CFR 372) Hazard Categories: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act: Isobutyl Acetate in this product is listed as Hazardous Substances under the CWA

Clean Air Act: Isobutyl Acetate in this product is listed as Hazardous Substances under the CCA.

California Prop 65: This product contains no chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 · OTHER INFORMATION

MSDS Revision Date: December 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 1

Flammability: 3

Reactivity: 0

The data in this Safety Data Sheet relates to the specific material designated and does not relate to its use in combination with any other material or process. The data contained is believed to be correct. However, since conditions of use are outside our control it should not be taken as warranty or representation for which Chemical Distribution Solutions assumes legal responsibility. This information is provided solely for your consideration, investigation, and verification.