SECTION 1 · COMPANY AND PRODUCT IDENTIFICATION

PRODUCT

Product Name: MINERAL OIL NF-70 Control Number: 00087 Product Description: Base Oil

COMPANY IDENTIFICATION

Supplier: Chemical Distribution Solutions 1125 Oak St. Ste. 303 Conway, AR 72032

24 Hour Emergency Telephone:(800) 424-9300 CHEMTRECGeneral Information:(501) 978-1111

SECTION 2- HAZARDS IDENTIFICATION

GHS Classification: [Health]

[Environmental]

[Physical]

CHEMICAL DISTRIBUTION

GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

Not a hazardous substance or mixture.

Pictograms

Signal Word: Warning

Hazard statement(s)

Precautionary statement(s)

SECTION 3 · COMPOSITION / INFORMATION ON INGREDIENTS		
CHEMICAL NAME	CAS Number	%WT
White Mineral Oil	8042-47-5	100

SECTION 4 - FIRST AID MEASURES

FIRST AID PROCEDURES:

Eye Contact: Flush eyes with water for at least 15 minutes. Seek medical attention if symptoms develop and persist.

Skin Contact: Wash with soap and water. Seek medical attention if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Seek medical attention if symptoms appear.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

CHEMICAL DISTRIBUTION

SECTION 5 · FIRE FIGHTING MEASURES

Suitable Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. **Hazardous combustion products:** Oxides of carbon and various hydrocarbons

Fire Fighting Procedures: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Unusual Fire and Explosion Hazards: Containers can build up pressure if exposed to heat and/or fire. Use water spray to keep fire-exposed containers cool. Containers may rupture in the heat of a fire.

SECTION 6 - ACCIDENTAL RELEASE and DISPOSAL MEASURES

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal. **Large Spill:** Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV.

SECTION 7 - STORAGE AND HANDLING

Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not breathe gas/fumes/ vapor/spray. Keep away from incompatibles such as oxidizing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 24°C (75.2°F).

SECTION 8 · EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated below. The level of protection and types of controls will vary depending upon potential exposure conditions.

Exposure Limits: White Mineral Oil 5 mg/m3 ACGIH; 5 mg/m3 OSHA

Personal Protective Equipment (PPE):

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133.

Skin: If prolonged or repeated skin contact is likely, wear appropriate protective gloves.

Clothing: Selection of protective clothing depends on work conditions, potential exposure conditions and may include gloves, boots, suits and other protective items.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

Respirators: Where adequate ventilation is not available an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. In confined areas, use a self-contained breathing apparatus.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: 320 °F Autoignition Temperature: No available data Boiling Point Range: No available data Melting Point/Freezing Point: No available data Vapor Pressure: 1mmHg Vapor Density (Air-1): >1 Appearance/Odor: Clear white liquid with mild odor. Flammability Limits: No available data Specific Gravity: 0.84 Volatile %: Nil Evaporation Rate (BuAc=1): No available data pH: Not Applicable Solubility in Water: Negligible

CHEMICAL DISTRIBUTION

SECTION 10 · STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use and temperature conditions. Conditions to Avoid: None known. Incompatible Materials: Strong oxidizing agents. Hazardous Polymerization: Will not occur.

SECTION 11 · TOXILOGICAL INFORMATION

Signs and Symptoms of Overexposure:

Skin: Contact can cause minor irritation.Eyes: Contact can cause minor irritation.Inhalation: Not likely to cause any discomfort. Excessive inhalation will result in difficulty in breathing.Ingestion: If swallowed this material may cause stomach upset.

Acute oral toxicity: LD50 rat: >5 g/kg Acute inhalation toxicity: LC50 rat: >5 mg/l Acute dermal toxicity: LD50 rabbit: >2 g/kg

SECTION 12 · ECOLOGICAL INFORMATION

Aquatic Toxicity: Not expected to be harmful to aquatic organisms. Bio-accumulative potential: Expected not to be readily biodegradable. However microbial activity upon this material will readily degrade it. Mobility: No available data.

SECTION 13 · DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

SECTION 14 · TRANSPORTATION

U.S. DEPARTMENT OF TRANSPORTATION (Road or Rail):

Proper Shipping Name: Not a Regulated DOT Material Hazard Class UN Number: Packaging Group:

CHEMICAL DISTRIBUTION

SECTION 15 · REGULATORY INFORMATION

US FEDERAL REGULATIONS

Comprehensive Environmental Response and Liability Act (CERCLA)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. The reportable quantity (RQ) for this material has not been established.

Toxic Substance Control Act (TSCA): All components of this product are listed on the TSCA inventory list.

SARA Section 311/312 (40 CFR 370) Hazard Categories:

No SARA hazards

SARA Section 313 (40 CFR 372) Hazard Categories:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act: This product contains no chemicals that are listed under the CWA.

Clean Air Act: This product contains no chemicals that are listed under the CAA.

California Prop 65: This product contains no chemicals known by the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16 · OTHER INFORMATION

MSDS Revision Date: September 2014

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

Health: 0 Flammability: 1 Reactivity: 0

The data in this Safety Data Sheet relates to the specific material designated and does not relate to its use in combination with any other material or process. The data contained is believed to be correct. However, since conditions of use are outside our control it should not be taken as warranty or representation for which Chemical Distribution Solutions assumes legal responsibility. This information is provided solely for your consideration, investigation, and verification.